

Pasta Processing Plant

VCP Spring-Loaded Pressure Relief Valves



9



Description ▼

VCP Pressure Relief Valves consist of a cylindrical casing with a bottom flange to be connected with a spigot welded on the silo roof, a disc-shaped inner steel lid for negative pressure operation held in position by a central spring rod, an outside steel ring for excess pressure kept in position by three spring rods, gaskets, and a weather protection cover.

Function ▼

Inside the VCP Pressure Relief Valve, helical springs keep the valve lids closed when the pressure value remains within the preset limits. The three outside spring rods keep the external ring-shaped lid firmly closed as long as the force generated by the pressure inside the silo does not exceed the spring force. Once the pressure exceeds the pre-set value, the lid is pushed up allowing pressure to escape. The smaller lid covers the central circular opening of the external lid from below. It is held in the middle by a single spring rod and is pressed onto the external lid by the normal air pressure inside the silo. In the event of suction pressure, the spring is compressed and allows the lid to drop. The air entering the silo from outside ensures rapid pressure balance and pushes the central lid back up into the "closed" position.



Application ▼

VCP Pressure Relief Valves are the last resort when abnormal pressure conditions endanger the silo structure. This is why sudden excess or suction pressure inside the silo must be dealt with instantaneously. Even though ideally a Pressure Relief Valve should never have to go into action, it must be efficient and reliable if needed. With tens of thousands of units installed worldwide, VCP Pressure Relief Valves have given evidence of being totally reliable under the most different conditions.

Benefits ▼

- ✓ Safety for OEM and user thanks to ATEX certification zone 21;
- ✓ No contamination due to metal steel discs and EPDM white seal;
- ✓ Used with different materials in the same configuration;
- ✓ Easy to handle and fit thanks to lightweight design and reduced overall dimensions;
- ✓ Quick maintenance due to few components;
- ✓ Easy maintenance thanks to small numbers of components.

Pasta Processing Plant

VCP Spring-Loaded Pressure Relief Valves



Technical Features / Performance ▼

- ▶ 304 stainless steel body (VCP...2C)
- ▶ Size 273mm (11 in) and 356mm (14 in)
- ▶ Weather protection cover in stainless steel
- ▶ ATEX certification (zone 21) and HSE British Guidelines
- ▶ Air volume up to 13,000 m³/h (7,650 cfm)
- ▶ Setting range: excess pressure from 300mm H₂O (0.44 PSI) up to 800mm H₂O (1.16 PSI)
- ▶ Setting range: negative pressure from -50mm H₂O (0.07 PSI) up to -100mm H₂O (0.15 PSI)
- ▶ No internal welding seams
- ▶ Equipped for inductive signalling sensors
- ▶ Protective bellows for springs
- ▶ White integral food-grade seal
- ▶ Small number of components
- ▶ Easy part replacement
- ▶ Lightweight and easy to handle
- ▶ Interchangeable discs

Overall Dimensions ▼

	Ø 273 mm	Ø 375 mm
A	400	525
B	356	468
C	125	175
D	120	120
E	325	400
Ø F	273	356
kg	9.5	23

