

Plastics Processing

ILT Rotary Level Indicators

13



Description ▼

ILT-type Bin Level Indicators have been designed for electric signalling by rotary action of minimum or maximum material level inside bins, hoppers or silos.

Function ▼

As long as material is present, the paddle of the ILT Bin Level Indicator does not rotate. As soon as the material level sinks below the paddle radius, rotation restarts activating other system components. The top or side-mounted indicators are commonly used for materials having a bulk density ranging between 0.5t/m^3 (0.02 lb per cu in) and 2t/m^3 (0.08 lb per cu in).



Applications ▼

Typically ILT Rotary Level Indicators are fitted on the vertical walls of a bin, silo or hopper at the desired maximum or minimum level. Equipped with an extension rod, they can also be mounted vertically into the roof plate.

Benefits ▼

- ✓ No product contamination due to the 304 stainless steel shaft; and measuring paddle and non-toxic plastic fittings;
- ✓ No product contact with the casing;
- ✓ Zone 20 /21 ATEX-certified;
- ✓ Adjustable via reset of force spring in 3 positions;
- ✓ Double threaded fitting ensures system compatibility;
- ✓ Use with different materials in one single configuration;
- ✓ Easy and quick installation and replacement;
- ✓ Compact overall dimensions;
- ✓ Lightweight due to casing in aluminium alloy;
- ✓ Maintenance-free;
- ✓ Cost-effective.



TOREX®



www.wamgroup.com

Plastics Processing




ILT Rotary Level Indicators



Technical Features / Performance ▼

- ▶ Voltages available: 24 V – 48 V (AC), 50-60 Hz;
110 V – 230 V (AC), 50-60 Hz; 24 V (DC)
- ▶ Signal output: Floating microswitch AC max. 250 V, 2 A
- ▶ Standard connection: thread G 1½" – G 2½"
- ▶ Enclosure: IP 66
- ▶ Working temperature inside vessel:
- 20 °C to 80 °C (- 4° F to 178° F)
- ▶ Vessel maximum pressure: max. 0.8 bar (12 PSI)
- ▶ Threaded fittings material: Plastic
- ▶ Rotating shaft and measuring paddle material: 304 stainless steel
- ▶ Casing material: Aluminium alloy
- ▶ Speed of measuring paddle: 1 rpm
- ▶ Friction clutch protection of the gearing of impacts of the measuring paddle
- ▶ Self-opening double paddle for light materials
- ▶ Flanged connection as option
- ▶ Modular shaft extension up to 3 metres (10 ft)
- ▶ External light

Overall Dimensions ▼



1: L = 500 / 1000